

Technical Data Sheet

PN1

porcher *SPORT*

ZI des Vallons
38110 La Tour du Pin Cedex (France)
Tel : +33 (0)4.74.82.25.36
Fax : +33 (0)4.74.82.25.11



DESCRIPTION

Fabric	70009
Finish	Overfinished and calendered
Yarn	PA 6.6 high tenacity - 33 dtex
Width	1680 mm
Pattern	Rip Stop
Internal ref.	70009 + width + PN1 + color shade
Length of rolls	300 lm

Utilization / End-uses

Parachute

Technical Specifications

Characteristics		Test Method	Unit	Tolerance
Weight		NFG 07/150	g/sqm	38,5-42,5
Count	warp	NF 1049-2	yarns/cm	49,6 min
	weft			
Tear Strength	warp	NF 13937-2	N	22 min
	weft			
Breaking strength	warp	NF 13934-1	N/5 cm	400 min
	weft			
Elongation	warp		%	22 min
	weft			
Air permeability	Tested under 127 Pa, 20 cm ²		ISO 9237	l/sqm/s
				15 max

Quality Specifications

	Nf G 07-163	mm	85
			50

Quality	Defects Criteria
Premium grade	< 7 defects / 100 ml
Standard grade	> 7 defects / 100 ml

Approvals	Development Department	Commercial Department	Quality Department

PORCHER SPORT undertakes that, on the day of delivery, its PRODUCT complies with the technical specification outlined in the corresponding technical data files and which were provided to the client. Nevertheless, PORCHER SPORT cannot be held liable for any damage resulting from handling, transportation, storage and/or maintenance conditions which might prove unsuitable to our fabric, in the event of any usage of the product other than that described in the technical file, for implementation conditions which do not respect good trade practices, nor for any errors or faults committed by the user, whether intentionally or not.